

'ZAMMORA' - Floor Care Sheet

General

- Zammora flooring is suitable for installation in almost any residential building.
- It can be installed over concrete slab or hard surface floors.
- However, wooden floors are sensitive to wet, extreme humidity and extreme drought. We do not advise these products are used in Bathrooms because of the inevitable regular direct contact with water.
- At Installation, the rule to apply in order to extend the lifetime of the floor is that relative atmospheric Humidity (RH) should ideally be between 45% and 60%.

Use In Kitchens

- Prevent direct water contact.

Aesthetic Nature

- Zammora is made entirely of genuine, aesthetic and beautifully natural wood.
- In order to maintain its beauty, placing a quality doormat on both the inside and the outsides of entrances are recommended to prevent scratches caused by abrasive grit and dirt.
- Being made of genuine wood, every board is unique and therefore no photographs or samples can be exactly reproduced with exact colours, grains and tints of the genuine article.

Do's

- Support Furniture and heavy appliances with wide bearing non staining glides or casters.
- Move appliances and furniture into place by sliding them slowly over the floor on a clean piece of carpet turned upside down.
- Place rugs in high traffic areas to make long term maintenance easier and less expensive.

Dont's

- Do not wax the floor - Do not wet mop the floor.
- Avoid spiked heel shoes, pebbles, sand and other abrasive.
- Do not use soap or detergents on the floor and never pour water directly onto the floor.
- Do not use ammonia-based cleaners.

Finishing

- Aluminium Oxide - Consult a professional about refinishing your floor.

Resistant Against

- | | | | |
|-----------|----------------|------------------|-----------------------|
| • Acetone | * Fruit Juices | * Coffee and Tea | * Alcoholic Beverages |
| • Thinner | * Fat and Oil | * PVC-Sealants | |

Recommended Maintenance

- For general cleaning use a broom, just-damp mop or vacuum.
- Keep grit off the floor, sweep or vacuum regularly and keep door mats well shaken
- Wipe up spills promptly with a dry cloth. Use a slightly dampened cloth for sticky spills.
- Should staining occur from food, ink, grease, lipsticks, cigarette burns, crayon, wax and nail polish – the following should be done:
 - Wipe with a damp cloth first and If unsuccessful use a mild detergent (ph 6 – 8 %)
 - If stain persists then use acetone. Under normal circumstances acetone should be able to remove the above-mentioned stains without fail.
 - **Avoid** however, scrubbing with an abrasive piece of material and using strong detergents.

Installing Over Underfloor Heating

- It can be installed over properly installed heated slabs that do not heat to a temperature over 80 degrees Fahrenheit, and have been active for at least three weeks prior to installation.
- Place the flooring in the room, stripped of any plastic coverings, to acclimatise slowly over 2 – 3 days. During this time turn the temperature up slowly to a maximum of 27 degrees.
- Slowly turn the temperature down over several hours to two thirds of the maximum temperature to commence installation. Maintain at this temperature whilst installation is completed.

- Post Installation – Increase the temperature by approx 1 degree per day to a maximum SUBFLOOR temperature of 27 degrees. Note: This must be a subfloor temperature and not a room temperature. Then turn down again to comfort level equally slowly.
- Zamorra does not advise Merbau, Beech or Kempas be laid over a radiant heated sub-floor. Walnut is not guaranteed over U/F heating.